

## **CPL-2W (-60°C to +200°C) – For Pilot Applications.**

Operating temperature range	-60°C to +200°C
Temperature control accuracy	±0.5°C
Temperature display	7" touch screen display
Temperature display resolution	0.01
Internal / Jacket temperature sensor	3-wire RTD PT-100 sensor
External / Process sensor required	3-wire RTD PT-100 sensor
Controller type	PID, Process / Jacket control selectable
Communication / Interface	RS-485 Mod bus, Ethernet.
Alarm message	Indicative
Type of Cooling	Refrigerated
Refrigerant	R-404a, CFC free
Cooling power with	Methanol
@ 0 °C	12 kW
@-40 °C	6 kW
@-60 °C	1.5 kW
Type of Heating	Electrical
Heating Power	9 kW
Machine standard version	Water-Cooled
Cooling water flow minimum	1200 l/hr
Cooling water pressure	3 bar
Cooling water temperature	10~30°C
Cooling water connection	1" hose nipple
Circulation Pump maximum flow	80~90 l/min
Circulation Pump maximum pressure	1.5 bar
Machine end connection	M42x1.5 Male
Machine overall dimension (W x D x H)	750 x 790 x 1500 mm
MOC	Complete SS-304 construction
Power supply	3-Phase, 420V AC, 50 Hz
Maximum current	50A
Ambient temperature condition	10°C ~ 40°C
<b><u>Standard Safety Features:</u></b>	
Phase reversal prevention	Cut-off, Indication / Message, Manual reset
Over temperature protection	Cut-off, Indication / Message, Auto reset
Compressor over pressure	Cut-off, Indication / Message, Manual reset
Compressor over heat	Cut-off, Indication / Message, Auto reset

- 
- Since development is a continuous process, above specifications can change without prior notice
  - The temperature mentioned above is at outlet of the machine hence temperature inside the load may vary due to various factors like process design, distance, head, insulation etc.