## 1 ltr Lab Scale ANFD



Model	ANFD 1	
Filter Area Material of Construction Volume	0.005m <sup>2</sup> Wetted parts: SS 316 Non-wetted parts: SS304 1 Ltr.	
Design Pressure	Vessel: -1 to 4 bar	Jacket : 6 bar
Design Temperature	Vessel: -20°C to 150°C	Jacket: -20°C to 150°C
Nozzles & fittings	<ul> <li>Compound pressure gauge (-1 to 6 bar),</li> <li>pressure relief valve,</li> <li>Ball valve with removable funnel for slurry inlet,</li> <li>Dry air/N<sub>2</sub> purging valve,</li> <li>vent valve,</li> <li>Filtrate outlet/drain valve,</li> <li>K-type temperature sensor.</li> <li>Note: All valves shall be ball valves, made of SS316 &amp; valve end connection shall be Tri-clover connection.</li> </ul>	
Vessel and Lid sealing	Viton O-ring with quick opening TC clamp.	
Agitation	Manual agitation arrangement with effortless clockwise and anti-clockwise movement.	
Shaft sealing	Mechanical seal.	
Filter Basket	5μm pore size filter basket made of SS316 with support.	
Stirrer	2 bladed turbine impeller	
Heating	SS304 jacket	
Electric Control Panel	SS panel with digital temperature indicator and high temperature alarm.	
Power supply	1φ, 220VAC, 50Hz	
System Mounting	Table Top	