



100 ltr Lab Scale ANFD

Model	ANFD 5	
Filter Area	0.20 m ²	
Material of Construction	Wetted parts: SS 316 Non-wetted parts: SS304	
Volume	100 Ltr.	
Design Pressure	Vessel: -1 to 4 bar	Jacket : 6 bar
Design Temperature	Vessel: -20°C to 150°C	Jacket: -20°C to 150°C
Nozzles & fittings	<ul style="list-style-type: none"> • Compound pressure gauge (-1 to 6 bar), • pressure relief valve, • Ball valve with removable funnel for slurry inlet, • Dry air/N₂ purging valve, • vent valve, • Filtrate outlet/drain valve, • K-type temperature sensor. <p>Note: All valves shall be ball valves, made of SS316 & valve end connection shall be Tri-clover connection.</p>	
Vessel and Lid sealing	Viton O-ring with quick opening TC clamp.	
Agitation	Motorized agitation arrangement with bi-directional rotation and effortless up-down movement	
Shaft sealing	Mechanical seal.	
Filter Basket	5µm pore size filter basket made of SS316 with support.	
Stirrer	2 bladed turbine impeller	
Heating	SS304 jacket	
Electric Control Panel	SS control panel with digital temperature indicator and high temperature alarm with variable frequency drive for 5 to 25 rpm infinitely variable speed, digital rpm indicator and bi-directional rotation.	
Power supply	1φ, 220VAC, 50Hz	
System Mounting	Table Top	